

Distributed by:



HIGH PRESSURE CLEANERS

Raider 2465 psi (max) • 8 l/pm







Single Phase Cold Water

Semi-frequent

The Jetwave® Raider™ is suited for those entry level pressure cleaning jobs i.e. bikes, driveway and vehicles. For semi-frequent use, the Raider™ will help around the house and jobs onsite incorporating quality global components.



FIELDS OF APPLICATION

Concrete and Landscaping Household and Path Cleaning Agricultural Equipment Car and Equipment Yards Motorcross Bike Wash-down





STANDOUT FEATURES



Quality solid brass pump head.



Quality induction electric motor with thermal protection.



Built in hose reel including 10m steel armoured hose.



Stainless steel straight lance with brass snap coupling for easy change over nozzle selection.



Total Stop Protection SystemTM (TSS) for operational longevity.



Quality brass water inlet connection.



0°, 15, 25, 40 and low pressure snap-on nozzle selection.



Ergonomic spray gun with stainless steel back part lance and quick coupling. connector.



Jetwave Group

72–74 Richmond Road
Keswick I Adelaide
South Australia I 5035 I AU

+61 8 8371 3599

sales@jetwave.com.au

jetwave.com.au

Quality - Induction motor great performance with high durability.

Ready - Onboard detergent tank.

hose.

Convenient - Built in hose reel including 10m steel armoured

Easy - Snap on nozzle selection.

Long Lasting - Full brass pump head.

Manoeuvrable - Light and easy to move.

STANDARD EQUIPMENT



OPTIONAL ACCESSORIES

1. 10m Additional Steel Armoured Hose	p/n	INCLUDED
2. Turbo Head	p/n	JWA303

Product Code	p/n	11183	
TECHNICAL DATA			
Working Pressure	psi / bar	1900 / 130	
Maximum Working Pressure	psi / bar	2465 / 170	
Flow Rate	l/pm	8	
Maximum Flow Rate	l/pm	8.5	
Max Water Inlet Temp	°c	55° / 130°	
INTENDED APPLICATION			
Usage Frequency	hours / type	1 -2 daily / Intermittent	
Category of Dirt / Debris	type	Light	
ELECTRICAL FEATURES			
Motor	type	Induction	
Power Supply	Ph / V / Hz	1 / 230 / 50	
Absorbed Power	kW / Pole (rpm)	2.5 / 2 (2800)	
Cable Length	metres	10	
Control	type	Total Stop System TM (TSS)	
HYDRAULIC FEATURES			
Pump / Head / Pistons	type	Axial / Brass / Ceramic Coated	
Pump Speed	rpm	2800	
Unloader Valve	type	Integral	
Orifice / Nozzle	size	03	
OTHER FEATURES			
Adjustable Pressure	y / n	N	
Frame Structure	type	2-Wheel Trolley	
Onboard Accessory Storage	y / n	Υ	
Detergent Injector	y / n	Y - Onboard tank adjustable dial	
DIMENSIONS & WEIGHT			
Approx Weight	kg	21.5 unit / 23 boxed	
Unit Dimensions	mm	780(L) x 590(W) x 900(H)	
Boxed Dimensions	mm	900(L) x 680(W) x 700(H)	

The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement.

year

type: pieces

AS: 9 / Euro: 6

Number per Pallet

WARRANTY

Product