

The therm C-Series

Trigger gun with safety catch and lance replaces one-piece design

1



Integrated Hose Drum (Optional)

Practical design and features a longer length high-pressure hose complete with folding crank

#### **Cleaning Agent Intake** Injector system for dispensing of cleaning agents

**Parking brake** For a secure stationary position

sition

CA11/130

Operating panel arranged for good overview with adjustable rotary thermostat for

controlling the water temperature

# Removable covers

Protect the mechanical components from environmental factors and provide convenient access

### Pressure regulation

Fully adjustable control allows operating pressures to be set to suit any task

## **EVEN BETTER NOW!**

#### MAKING A CHANGE IS EASY

The therm-CA are now being supplied with a two piece trigger gun with safety catch and lance with threaded fittings.

		0
Technical specifications		
Operating pressure adjustable	psi	1885
Max. admissible overpressure	psi	2100
Connected load	V / ~ / Hz / A	230 / 1 / 50 / 15
Motor speed	Rpm	1400
Water output	l/min l/h	11 660
kW		2.3
Volume water tank	ļ	4
Hot water output adjustable	°C	12-80
Steam level	°C	140
Heating output	kW	55
Fuel tank	I	25
Power supply cable	m	5
Dimensions L x W x H	mm	800 / 600 / 980
Weight	kg	171
Detergent Injector		•
Equipment		
Hose drum		-
Steel braided high-pressure hose	m	10
Trigger gun with safety catch	Model	M2000
Stainless steel lance with flat jet nozzle	Nozzle size	D25045





