

THE POWER TO BE PRESENT



DOMETIC CFX3 SPECIFICATIONS	DOMETIC CFX3 35 Compressor fridge or freezer	DOMETIC CFX3 45 Compressor fridge or freezer	DOMETIC CFX3 55 Compressor fridge or freezer	DOMETIC CFX3 55IM Compressor fridge or freezer, ice maker	DOMETIC CFX3 75DZ Compressor fridge and freezer	DOMETIC CFX3 95DZ Compressor fridge and freezer
Storage capacity (l)	36	46	55	53	75	94
Can count (375ml)	50	67	85	83	113 (68/45)	133 (81/52)
Voltage	12/24 V DC and 100 – 240 V AC	12/24 V DC and 100 – 240 V AC	12/24 V DC and 100 – 240 V AC	12/24 V DC and 100 – 240 V AC	12/24 V DC and 100 – 240 V AC	12/24 V DC and 100 – 240 V AC
USB charging outlet	5 V / 2 A rating	5 V / 2 A rating	5 V / 2 A rating	5 V / 2 A rating	5 V / 2 A rating	5 V / 2 A rating
Power consumption (DC 12 V)	Average current draw x running time. Average 0.98 Ah/h (@12 V, 4°C set, 32°C ambient, Bluetooth on, WiFi off)	Average current draw x running time. Average 1.03 Ah/h (@12 V, 4°C set, 32°C ambient, Bluetooth on, WiFi off)	Average current draw x running time. Average 1.10 Ah/h (@12 V, 4°C set, 32°C ambient, Bluetooth on, WiFi off)	Average current draw x running time. Average 1.20 Ah/h (@12 V, 4°C set, 32°C ambient, ice maker on/maintenance, Bluetooth on, WiFi off)	Average current draw x running time. Average 3.04 Ah/h (@12 V, 4°C (large), -15°C (small), 32°C ambient, Bluetooth on, WiFi off)	Average current draw x running time. Average 3.57 Ah/h (@12 V, 4°C (large), -15°C (small), 32°C ambient, Bluetooth on, WiFi off)
Temperature range	+10 °C to -22 °C (Minimum setting of -18 °C recommended for normal usage)	+10 °C to -22 °C (Minimum setting of -18 °C recommended for normal usage)	+10 °C to -22 °C (Minimum setting of -18 °C recommended for normal usage)	+10 °C to -22 °C (Minimum setting of -18 °C recommended for normal usage)	+10 °C to -22 °C (Minimum setting of -18 °C recommended for normal usage)	+10 °C to -22 °C (Minimum setting of -18 °C recommended for normal usage)
Insulation	CFC-free PU foam, generous thickness	CFC-free PU foam, generous thickness	CFC-free PU foam, generous thickness	CFC-free PU foam, generous thickness	CFC-free PU foam, generous thickness	CFC-free PU foam, generous thickness
System	Dometic Waeco ACV20DC compressor with integrated VM SO <sup>3</sup> electronics, low voltage protection, adjustable for leisure and starter battery, AC mains priority circuit, dynamically ventilated condenser, aluminium rollbond evaporator	Dometic Waeco ACV20DC compressor with integrated VM SO <sup>3</sup> electronics, low voltage protection, adjustable for leisure and starter battery, AC mains priority circuit, dynamically ventilated condenser, aluminium rollbond evaporator	Dometic Waeco ACV20DC compressor with integrated VM SO <sup>3</sup> electronics, low voltage protection, adjustable for leisure and starter battery, AC mains priority circuit, dynamically ventilated condenser, aluminium rollbond evaporator	Dometic Waeco ACV20DC compressor with integrated VM SO <sup>3</sup> electronics, low voltage protection, adjustable for leisure and starter battery, AC mains priority circuit, dynamically ventilated condenser, aluminium rollbond evaporator	Dometic Waeco ACV20DC compressor with integrated VM SO <sup>3</sup> electronics, low voltage protection, adjustable for leisure and starter battery, AC mains priority circuit, dynamically ventilated condenser, aluminium rollbond evaporator	Dometic Waeco ACV25DC compressor with integrated VM SO <sup>3</sup> electronics, low voltage protection, adjustable for leisure and starter battery, AC mains priority circuit, dynamically ventilated condenser, aluminium rollbond evaporator
Material	Cabinet & lid: polypropylene, Handles: aluminium alloy, Hinges: aluminium alloy & stainless steel	Cabinet & lid: polypropylene, Handles: aluminium alloy, Hinges: aluminium alloy & stainless steel	Cabinet & lid: polypropylene, Handles: aluminium alloy, Hinges: aluminium alloy & stainless steel	Cabinet & lid: polypropylene, Handles: aluminium alloy, Hinges: aluminium alloy & stainless steel	Cabinet: steel & polypropylene, Lid: polypropylene, Handles: aluminium alloy, Hinges: aluminium alloy & stainless steel	Cabinet: steel & polypropylene, Lid: polypropylene, Handles: aluminium alloy, Hinges: aluminium alloy & stainless steel
Colour	Body: dark grey; Lid: light grey	Body: dark grey; Lid: light grey	Body: dark grey; Lid: light grey	Body: dark grey; Lid: light grey	Body: dark grey; Lid: light grey	Body: dark grey; Lid: light grey
Weight (kg)	16.9	18.7	20.4	21.3	27.8	29.8
Dimensions (W x H x D) mm	398 x 407 x 694	398 x 476 x 694	720 x 480 x 455	720 x 480 x 455	892 x 472 x 495	962 x 472 x 530
Quality features	Bluetooth & WiFi enabled, detachable lid, interior light, drain plug, CFX3 VM SO <sup>3</sup> electronics, USB port, TFT LCD display (dimnable), 3-stage battery protection, anti-condensation heating, 4 x M6 nutserts in base	Bluetooth & WiFi enabled, detachable lid, interior light, drain plug, CFX3 VM SO <sup>3</sup> electronics, USB port, TFT LCD display (dimnable), 3-stage battery protection, anti-condensation heating, 4 x M6 nutserts in base	Bluetooth & WiFi enabled, detachable/reversible lid, interior light, drain plug, CFX3 VM SO <sup>3</sup> electronics, USB port, TFT LCD display (dimnable), 3-stage battery protection, anti-condensation heating, 4 x M6 nutserts in base	Bluetooth & WiFi enabled, ice maker, detachable/reversible lid, interior light, drain plug, CFX3 VM SO <sup>3</sup> electronics, USB port, TFT LCD display (dimnable), 3-stage battery protection, anti-condensation heating, 4 x M6 nutserts in base	Bluetooth & WiFi enabled, dual zone refrigeration or freezing, detachable/reversible lids, interior lights, drain plugs, CFX3 VM SO <sup>3</sup> electronics, USB port, TFT LCD display (dimnable), 3-stage battery protection, anti-condensation heating, 4 x M6 nutserts in base	Bluetooth & WiFi enabled, dual zone refrigeration or freezing, detachable/reversible lids, interior lights, drain plugs, CFX3 VM SO <sup>3</sup> electronics, USB port, TFT LCD display (dimnable), 3-stage battery protection, anti-condensation heating, 4 x M6 nutserts in base
Scope of delivery	DC and AC connection cables, removable wire basket, spring-loaded carrying handles	DC and AC connection cables, 2 x removable wire baskets, spring-loaded carrying handles	DC and AC connection cables, 2 x removable wire baskets, spring-loaded carrying handles	DC and AC connection cables, 2 x removable wire baskets, spring-loaded carrying handles, ice maker housing with lid, 2 x ice trays with lid	DC and AC connection cables, 3 x removable wire baskets, spring-loaded carrying handles	DC and AC connection cables, 3 x removable wire baskets, spring-loaded carrying handles
Ref No.	9600025299	9600025300	9600025301	9600025302	9600025303	9600025304