



» Generator set data sheet

**Model:** C66 D5 (S3.8)  
**Frequency:** 50  
**Fuel Type:** Diesel

Spec sheet:	SS27-CPGK
Noise data sheet (Open/enclosed):	ND50-CS550
Airflow data sheet:	AF50-550
Derate data sheet (Open/enclosed):	TBD
Transient data sheet:	TD50-550

Fuel consumption	Standby				Prime			
	kVA (kW)				kVA (kW)			
Ratings	66 (52.8)				60 (48)			
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
gph	1.1	1.8	2.7	3.5	1.0	1.6	2.4	3.2
L/hr	5.00	8.20	12.20	16.10	4.50	7.40	11.00	14.70

Engine	Standby Rating	Prime Rating
Engine manufacturer	Cummins	
Engine model	S3.8 G7	
Configuration	Inline 4-Cylinder Diesel	
Aspiration	Turbocharged and Charge Air Cooled	
Gross engine power output, kWm	64.9	59.6
BMEP at set rated load, kPa	1379	1255
Bore, mm	97	
Stroke, mm	128	
Rated speed, rpm	1500	
Piston speed, m/s	6.4	
Compression ratio	17.5 : 1	
Lube oil capacity, L	9	
Overspeed limit, rpm	1650	
Regenerative power, kW	5.96	
Governor type	Mechanical as std	
Starting voltage	12V Volts DC	

Fuel flow	
Maximum fuel flow, L/hr	22.88
Maximum fuel inlet restriction, mm Hg	3.99
Maximum fuel inlet temperature (°C)	40

## Air

	Standby Rating	Prime Rating
Combustion air, m <sup>3</sup> /min	4.60	4.30
Maximum air cleaner restriction, kPa	6.2	

## Exhaust

Exhaust gas flow at set rated load, m <sup>3</sup> /min	4.9	4.5
Exhaust gas temperature, °C	509	493
Maximum exhaust back pressure, kPa	6.7	

## Standard set-mounted radiator cooling

Ambient design, °C	55	
Fan load, KW <sub>m</sub>	2 +/- 1	
Coolant capacity (with radiator), L	15	
Cooling system air flow, m3/sec @ 12.7mmH2O	1.9	
Total heat rejection, BTU/min	5543	4993
Maximum cooling air flow static restriction mmH2O	12.7	

## Weights\*

	Open	Enclosed
Unit dry weight kgs	1005	1455
Unit wet weight kgs	1165	1585


\* Weights represent a set with standard features. See outline drawing for weights of other configurations

## Dimensions


	Length	Width	Height
Standard open set dimensions	2115	1044	1516
Enclosed set standard dimensions	2600	1115	1795

## Genset outline

### Open set



### Enclosed set



Outlines are for illustrative purposes only. Please refer to the genset outline drawing for an exact representation of this model.

Alternator data

Connection <sup>1</sup>	Temp rise °C	Duty <sup>2</sup>	Alternator	Voltage
Wye -3 phase	163/125	S/P	UCI22 4F	380-415
Wye -3 phase	150/105	S/P	UCI22 4G	380-415

Ratings definitions

Emergency Standby Power (ESP)	Limited-Time running Power (LTP):	Prime Power (PRP)	Base Load (Continuous) Power (COP)
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514.

Formulas for calculating full load currents:

Three phase output

$$\frac{\text{kW} \times 1000}{\text{Voltage} \times 1.73 \times 0.8}$$

Single phase output

$$\frac{\text{kW} \times \text{SinglePhaseFactor} \times 1000}{\text{Voltage}}$$