# GHG7000E

**PORTABLE POWER** 



## Technical

Model Type Speed Phase/Voltage Frequency Max power kW Continuous Output Noise Level (dBA @ 7m) Frame

GHG7000E Portable 3000 RPM 1/240 50 Hz 7.0kW 8.0kVA 72 Extra Large roll frame

GHG 7000E

#### Engine

Manufacturer Engine Model Type Starting Fuel Run Time HP 3000 rpm cont Cubic Capacity Oil Capacity Honda GX390E O.H.V. Recoil & Electric start LPG Approx 3-4hrs based on P/9kg Cylinder (18ltrs LPG) 8.0 HP 389 Cm3 1.1 L

#### Alternator

Alternator Brand Type Harmonic Distortion Protection Class Insulation Class Meccalte Brushless Less than 5% IP 23 Class H

Outlets	
Outlet	10amp + 15amp switched with thermal overload
Dimensions & Weight	
Length	85 Cm

Length	85 CM
Width	57 Cm
Height	60 Cm
Weight	80 Kg

### Options

Outlets Protection Wheel kits Frames Alternators

Weather protected IP33 & Weatherproof IP66 RCD/ELCB IP30 or IP66 Two wheel or four wheel Extra large Roll Frames Oversized, Single or Three Phase

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.