



POWERED by
HONDA™

SPECIFICATION SHEET

GX200

MODEL	GX200
TYPE	4-stroke, overhead valve, single-cylinder, horizontal shaft
BORE & STROKE	68 x 54 mm
DISPLACEMENT	196 cm ³
COMPRESSION RATIO	8.5:1
NET POWER	4.1kW (5.5HP) at 3,600 rpm
CONTINUOUS RATED POWER	3.7kW (5.0HP) at 3,600 rpm
MAXIMUM NET TORQUE	12.4 Nm at 2,500 rpm
IGNITION SYSTEM	Transistorised magneto ignition
STARTING SYSTEM	Recoil (Electric Starter Optional)
COOLING SYSTEM	Forced-Air
PTO SHAFT ROTATION	Counter-clockwise (from P.T.O. side)
FUEL CONSUMPTION AT RATED POWER	1.7 L/h at 3,600 rpm
RECOMMENDED FUEL	Unleaded
LUBRICATION SYSTEM	Splash
RECOMMENDED OIL	10W/30 API SG
OIL CAPACITY	0.6l
FUEL TANK CAPACITY	3.1l
DIMENSIONS	313 x 376 x 346mm
DRY WEIGHT	16.2kg
OTHER OPTIONS	2:1 Reduction - 2:1 Reduction with Clutch - 6:1 Reduction

