



POWERED by
HONDA™

SPECIFICATION SHEET

GX270

| | |
|--|---|
| MODEL | GX270 |
| TYPE | 4-stroke, overhead valve, single-cylinder, horizontal shaft |
| BORE & STROKE | 77 x 58mm |
| DISPLACEMENT | 270 cm ³ |
| COMPRESSION RATIO | 8.2:1 |
| NET POWER | 6.0kW (8.0HP) at 3,600 rpm |
| CONTINUOUS RATED POWER | 5.1kW (6.8HP) at 3,600 rpm |
| MAXIMUM NET TORQUE | 17.7 Nm at 2,500 rpm |
| IGNITION SYSTEM | Transistorised magneto ignition |
| STARTING SYSTEM | Recoil (Electric Starter Optional) |
| COOLING SYSTEM | Forced-Air |
| PTO SHAFT ROTATION | Counter-clockwise (from P.T.O. side) |
| FUEL CONSUMPTION AT RATED POWER | 2.5 L/h at 3,600 rpm |
| RECOMMENDED FUEL | Unleaded |
| LUBRICATION SYSTEM | Splash |
| RECOMMENDED OIL | 10W/30 API SG |
| OIL CAPACITY | 1.1l |
| FUEL TANK CAPACITY | 5.3l |
| DIMENSIONS | 380 x 430 x 410mm |
| DRY WEIGHT | 25kg |
| OTHER OPTIONS | 2:1 Reduction - 2:1 Reduction with Clutch - 6:1 Reduction |

