



POWERED by
HONDATM

SPECIFICATION SHEET

GX340

MODEL	GX340
TYPE	4-stroke, overhead valve, single-cylinder, horizontal shaft
BORE & STROKE	82 x 64 mm
DISPLACEMENT	337cm ³
COMPRESSION RATIO	8.0:1
NET POWER	7.1kW (9.5HP) at 3,600 rpm
CONTINUOUS RATED POWER	5.8kW (7.8HP) at 3,600 rpm
MAXIMUM NET TORQUE	22.1 Nm at 2,500 rpm
IGNITION SYSTEM	Transistorised magneto ignition
STARTING SYSTEM	Recoil (Electric Starter Optional)
COOLING SYSTEM	Forced-Air
PTO SHAFT ROTATION	Counter-clockwise (from P.T.O. side)
FUEL CONSUMPTION AT RATED POWER	3.0 L/h at 3,600 rpm
RECOMMENDED FUEL	Unleaded
LUBRICATION SYSTEM	Splash
RECOMMENDED OIL	10W/30 API SG
OIL CAPACITY	1.1l
FUEL TANK CAPACITY	6.1l
DIMENSIONS	405 x 450 x 443mm
DRY WEIGHT	30kg
OTHER OPTIONS	2:1 Reduction

