

GYDWS180EHD



PORTABLE POWER







Technical

Model Type Speed Phase/Voltage Frequency Power kVA / kW Welder Duty Cycle 60% Strike Voltage Compressor Compressor Tank Size Battery Charger Engine	GYDWS180EHD Portable 3000 RPM 1/240 50 Hz 6.5kVA / 5.2kW 180 amp AC 75 V 218 LPM 3 Hp 27-29 litres 12 VDC 10 amp
Manufacturer Engine Model Starting Fuel Run Time Consumption Tank Capacity HP 3000 rpm Cubic Capacity Oil Capacity Alternator	Yanmar L100 Electric and Recoil start Diesel 3.3 hr 1.75 L/h 5.5 L 8.8 406 Cm3 1.65 L
Alternator Brand Type Harmonic Distortion Protection Class Insulation Class Dimensions & Weight	Sincro Brushless Less than 5% IP 23 Class H
Length Width Height Weight Accessories	96 Cm 70 Cm 70 Cm 130 Kg
Outlet Leads Options	10amp + 15amp switched with thermal overload 5m welding leads with hand piece & earth clamp
Outlets Protection Wheel kits	Weather protected IP33 & Weatherproof IP66 RCD/ELCB IP30 or IP66 Four wheel
Long Range Tank Welding Leads VRD	15 Litre Capacity Extra Length Welding Protection

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.