

Model PLGCM100S Speed 1500 RPM Phase/Voltage 3, 415 Frequency 50 Hz Stdby Power 110kVA / 88 kW Prime Output 100kVA / 80 kW Noise Level @ 7m 73 dB(A) Fuel Capacity 550 Litres Length 2.86m Width 1.11m Height 1.965m Weight 2035 kg

Engine

Manufacturer Cummins Diesel
Engine Model 6BT5.9G1
Type & Cylinder 4 Stroke – 4 L
Induction Turbocharged
Fuel Consumption
22L @ 100%, 17L @ 75%, 11L @ 50% Load
Coolant Capacity 10.5 L
Governor Mechanical
Cubic Capacity 5.9 L
Oil Capacity 16 L

Canopy

Emergency Stop External

Skid Bunded fuel tank with fork lift pockets and skid tie down points Canopy Centre lift, lockable doors with control panel viewing window Finish Heavy duty powder coat finish white canopy with a black base

Controls

Controller DeepSea 7320 with LCD Metering Circuit Breaker 3 Pole Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Mecc Alte ECP34-2S4A
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23

Insulation Class Class H

Options

Outlets Single or 3 Phase options
PMG option
Mine spec
Synchronising controls
Jacket water heater
Auto transfer switch options