



Genette

GKM10S

Model GKM10S
Type Medium Duty
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 11kVA / 9.0kW
Prime Output 10kVA / 8.0kW
Noise Level (dBA @ 7m) 59dB(A)
Fuel Capacity 33 Litres

Length 1.5m
Width 0.68m
Height 1.081m
Weight 528 kg

Engine

Manufacturer Kubota Diesel
Engine Model D1105-BG
Type & Cylinder 4 Stroke – 3 L
Induction Naturally Aspirated
Fuel Consumption
3L @ 100%, 2.2L @ 75%
Coolant Capacity 5.0 L
Governor Mechanical
Cubic Capacity 1.123 L
Oil Capacity 5.1 L

Options

Outlets 3 Phase 20amp IP66 with CB
Outlets Single Phase
3 x 15amp IP66 with RCD MCBO

Controls

Controller Remote Start with Analog Metering
Circuit Breaker Four Pole
Battery isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Mecc Alte ECP2VS/4
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop

