



Genette



PLGCM150S

Model PLGCM150S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 165kVA / 132kW
Prime Output 150kVA / 120kW
Noise Level 73 dB(A)
Fuel Capacity 816 Litres

Length 3.26m
Width 1.122m
Height 2.085m
Weight 2318 kg

Engine

Manufacturer Cummins Diesel
Engine Model 6BTAA5.9G12
Type & Cylinder 4 Stroke – In-Line6
Induction Turbocharged Air to Air After Cooled
Fuel Consumption
34 L @ 100%, 26L @ 75%, 17L @ 50% Load
Coolant Capacity 10.4 L
Governor Electronic
Cubic Capacity 5.9 L
Oil Capacity 16.4 L

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre lift, lockable doors with control panel viewing window
Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External

Controls

Controller DeepSea 7320 with LCD Metering
Circuit Breaker 4 Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Mecc Alte ECP34-2L4A
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Options

Outlets Single or 3 Phase options
PMG option
Mine spec
Synchronising controls
Jacket water heater
Auto transfer switch options

