



Genette



GKM20S-1

Model GKM20S-1
Type Medium Duty
Speed 1500 RPM
Phase/Voltage 1, 240
Frequency 50 Hz

Stdby Power 22kVA / 18kW
Prime Output 20kVA / 16kW
Noise Level (dBA @ 7m) 61 dBA
Fuel Capacity 37 Litres

Length 1.9m
Width 0.75m
Height 1.084m
Weight 781 kg

Engine

Manufacturer Kubota Diesel
Engine Model V2203-BG
Type & Cylinder 4 Stroke – 4 L
Induction Naturally Aspirated
Fuel Consumption
5.0L @ 100%, 3.8L @ 75%
Coolant Capacity 8.2 L
Governor Mechanical
Cubic Capacity 3.9 L
Oil Capacity 8.7 L

Outlets

Outlets Single Phase
3 x 15amp IP66 with RCD MCBO
EBS PMG Option

Controls

Controller Remote Start with Analog Metering
Circuit Breaker Two Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Mecc Alte ECP32-2S/4
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop Fitted

