



Genette



GKM20S

Model GKM20S
Type Medium Duty
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 22kVA / 17.6kW
Prime Output 20kVA / 16kW
Noise Level (dBA @ 7m) 61 dBA
Fuel Capacity 37 Litres

Length 1.7m
Width 0.75m
Height 1.084m
Weight 702 kg

Engine

Manufacturer Kubota Diesel
Engine Model V2203-BG
Type & Cylinder 4 Stroke – 4 L
Induction Naturally Aspirated
Fuel Consumption
4.0L @ 100%, 3.2L @ 75%, 2.4L @ 50% Load
Coolant Capacity 8.2 L
Governor Mechanical
Cubic Capacity 3.9 L
Oil Capacity 9.7 L

Options

Outlets 3 Phase 1 x 32amp IP66 with CB
Outlets Single Phase
3 x 15amp IP66 with RCD MCBO
EBS PMG

Controls

Controller Remote Start with Analog Metering
Circuit Breaker Two Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Mecc Alte ECP28 M4A
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop Fitted

