

Model GKM30S Type Medium Duty Speed 1500 RPM Phase/Voltage 3, 415 Frequency 50 Hz Stdby Power 33kVA / 26kW Prime Output 30kVA / 24kW Noise Level (dBA @ 7m) 61 dBA Fuel Capacity 75 Litres

Length 1.9m Width 0.87m Height 1.146m Weight 840 kg

Engine

Manufacturer Kubota Diesel
Engine Model V3300-BG
Type & Cylinder 4 Stroke – 4 L
Induction Naturally Aspirated
Fuel Consumption
7.7 L @ 100%, 5.9 L @ 75%, 4.2 L @ 50% Load

Coolant Capacity 8.2 L Governor Mechanical Cubic Capacity 3.9 L Oil Capacity 13.2 L

Options

Outlets 3 Phase

1 x three phase, 1 x single phase Protection RCD/ELCB IP66 EBS PMG MX341 or MX321

Controls

Controller Remote Start with LCD Display Circuit Breaker Four Pole Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Mecc Alte ECP28 VL4A
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Canopy Centre Lift, lockable doors with control panel viewing window

Path Finish Heavy duty powder coat finish white canopy with a black base

Emergency Stop External Emergency Stop Fitted