GH12,000E-FBT AVR

🔜 GH12,000E-FBT AVR

Frame



PORTABLE POWER



Technical

Model	GH 12,000E-FBT AVR
Туре	Portable
Speed	3000 RPM
Phase/Voltage	1/240
Frequency	50 Hz
Max power kW	10 kW
Continuous Output	12.5 kVA
Noise Level (dBA @ 7m)	74
Frame	Skid Base with Roll Fra

Engine

Manufacturer **Engine Model** Туре Starting Fuel **Run Time Tank Capacity** HP 3000 rpm cont **Cubic Capacity Oil Capacity**

Honda GX630 O.H.V. Electric start Unleaded Petrol 12 hrs @60% 50 L 14.1 HP 688 Cm3 1.9 L

Alternator

Alternator Brand Type **Harmonic Distortion Protection Class Insulation Class**

Mecc Alte - AVR Brushless Less than 5% IP 23 Class H

Outlets

Outlet

2 x 15amp switched with thermal overload

Dimensions & Weight 105 Cm Length Width 55 Cm Heiaht 70 Cm Weight 155 Kg

Options

Outlets Protection Wheel kits Alternators Weather protected IP33 & Weatherproof IP66 RCD/ELCB IP30 or IP66 Four wheel Oversized, Single or Three Phase

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.