🔁) GH4000-AVR



**PORTABLE POWER** 



### Technical

Model	
Туре	
Speed	
Phase/Voltage	
Frequency	
Max power kW	
Continuous Output	
Noise Level (dBA @ 7m)	
Frame	1

GH4000-AVR Portable 3000 RPM 1/240 50 Hz 4.0kW 4.5kVA 72 Small roll frame

#### Engine

Manufacturer Engine Model Type Starting Fuel Run Time Tank Capacity HP 3000 rpm cont Cubic Capacity Oil Capacity Honda GX270 O.H.V. Recoil start Unleaded Petrol 3.2 hr @ 100%, 4.5hrs @60% 6 L 6.2 HP 270 Cm3 1.1 L

#### Alternator

Alternator Brand Type Harmonic Distortion Protection Class Insulation Class Mecc Alte - AVR Brushless Less than 5% IP 23 Class H

10amp + 15amp switched with thermal overload

# Dimensions & WeightLength67 CmWidth44 CmHeight48 Cm

50 Kg

0				
	-	41	•1	

Outlets Protection Frames

Alternators

Weight

**Outlets** 

Outlet

Standard (thermal overload protected), RCD + Weatherproof Outlets (IP66 rated) RCD/ELCB IP30 or IP66
Extra large Roll Frames Oversized, Single or Three Phase
overbized, billigie of three thate

## The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.