GH5000-AVR



PORTABLE POWER

Technical

GH 5000-AVR Model Type Portable Speed 3000 RPM Phase/Voltage 1/240 Frequency 50 Hz Max power kW 5.0kW **Continuous Output** 6.0kVA Noise Level (dBA @ 7m) 72

Frame Large Roll Frame

Engine

ManufacturerHondaEngine ModelGX340TypeO.H.V.StartingRecoil startFuelUnleaded Petrol

Run Time 3.0 hr @ 100%, 4.2hrs @60%

 Tank Capacity
 6.1 L

 HP 3000 rpm cont
 7.2 HP

 Cubic Capacity
 337 Cm3

 Oil Capacity
 1.1 L

Alternator

Alternator Brand Mecc Alte - AVR
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Outlets

Outlet 10amp + 15amp switched with thermal overload

Dimensions & Weight

 Length
 76 Cm

 Width
 50 Cm

 Height
 57 Cm

 Weight
 56 Kg

Options

Outlets Standard (thermal overload protected), RCD +

Weatherproof Outlets (IP66 rated)

ProtectionRCD/ELCB IP30 or IP66Wheel kitsTwo wheel or four wheelFramesExtra Large Roll Frames

Alternators Oversized, Single or Three Phase

Long Range Tank 15 Litre Capacity

Start Type Electric Start, Full AMF, Remote Start



