GH7000-AVR



GH7000-AVR



PORTABLE POWER



Technical

Model
Туре
Speed
Phase/Voltage
Frequency
Max power kW
Continuous Output
Noise Level (dBA @ 7m)
Frame

GH7000-AVR Portable 3000 RPM 1/240 50 Hz 7.0kW 8.0kVA 72 Extra Large Roll Frame

Engine

Manufacturer Engine Model Type Starting Fuel Run Time Tank Capacity HP 3000 rpm cont Cubic Capacity Oil Capacity Honda GX390 O.H.V. Recoil start Unleaded Petrol 2.6 hr @ 100%, 3.8hrs @60% 6.1 L 8.0 HP 389 Cm3 1.1 L

Alternator

Alternator Brand Type Harmonic Distortion Protection Class Insulation Class Mecc Alte - AVR Brushless Less than 5% IP 23 Class H

10amp + 15amp switched with thermal overload

Dimensions & Weight

Length	76 Cm	
Width	50 Cm	
Height	57 Cm	
Weight	80 Kg	

Options

Outlets

Outlet

Outlets Protection Wheel kits Frames Alternators Long Range Tank Standard (thermal overload protected), Weather protected IP33 & Weatherproof IP66 RCD/ELCB IP30 or IP66 Two wheel or four wheel Extra large Roll Frames Oversized, Single or Three Phase 15 Litre Capacity

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.