


# GH7000-LRT-RS



SUPPORT POWER

#### **Technical**

Model GH7000-LRT-RS

Type Portable
Speed 3000 RPM
Phase/Voltage 1/240
Frequency 50 Hz
Max power kW 7.0kW
Continuous Output 8.0kVA
Noise Level (dBA @ 7m) 72

Frame Extra Large roll frame

#### **Engine**

ManufacturerHondaEngine ModeliGX390TypeO.H.V.

Starting Recoil & Electric start + 2 wire Remote Start

Fuel Unleaded Petrol

**Run Time** 2.6 hr @ 100%, 3.8hrs @60%

Tank Capacity25 LHP 3000 rpm cont8.0 HPCubic Capacity389 Cm3Oil Capacity1.1 L

### **Alternator**

Alternator Brand Mecc Alte
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

# **Dimensions & Weight**

 Length
 85 Cm

 Width
 57 Cm

 Height
 60 Cm

 Weight
 80 Kg

#### **Remote Start**

**Controls** Remote Start 2 wire + Monicon GTR-168

**Connection** Wired to set via Three metre Cable Circuit Breaker

**Protection** Single Pole 32amp





## **Options**

**\_PG** Conversion to LPG

Extended Fuel Tank12L and 50 L Base Tank versionThree PhaseOption and oversized for motor startingBattery Charger12 vdc 3amp capacity 240v powered