

Model GK10S1 Type Heavy Duty Speed 1500 RPM Phase/Voltage 1, 240 Frequency 50 Hz Stdby Power 11kVA / 8.8kVV Prime Output 10kVA / 8.0kVV Noise Level (dBA @7m) 55dB(A) Fuel Capacity 100 Litres Length 1.93m Width 0.877m Height 1.30m Weight 681 kg

Engine

Manufacturer Kubota Diesel Engine Model D1105-BG Type & Cylinder 4 Stroke – 3 L Induction Naturally Aspirated Fuel Consumption 2.3L @ 100%, 1.9L @ 75%, 1.4L @ 50% Load Coolant Capacity 5.0 L Governor Mechanical Cubic Capacity 1.123 L Oil Capacity 5.1 L

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points Canopy Centre Lift, lockable doors with control panel viewing window Path Finish Heavy duty powder coat finish white canopy with a black base Emergency Stop External Emergency Stop

Controls

Controller Remote Start with Analog Metering Circuit Breaker Two Pole Battery isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford Pi044H Type Brushless Harmonic Distortion Less than 5% Protection Class IP 23 Insulation Class Class H

Outlets

Outlets Single Phase 3 x 15amp IP66 with RCD MCBO

Outlets EBS PMG