



Genette



GK10S

Model GK10S
Type Heavy Duty
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 11kVA / 8.8kW
Prime Output 10kVA / 8.0kW
Noise Level (dBA @ 7m) 55dB(A)
Fuel Capacity 100 Litres

Length 1.93m
Width 0.927m
Height 1.30m
Weight 693 kg

Engine

Manufacturer Kubota Diesel
Engine Model D1105-BG
Type & Cylinder 4 Stroke – 3 L
Induction Naturally Aspirated
Fuel Consumption
2.3L @ 100%, 1.9L @ 75%, 1.4L @ 50% Load
Coolant Capacity 5.0 L
Governor Mechanical
Cubic Capacity 1.123 L
Oil Capacity 5.1 L

Outlets

Outlets 3 Phase 20amp IP66 with CB
Outlets Single Phase
3 x 15amp IP66 with RCD MCBO

Options

EBS PMG

Controls

Controller Remote Start with Analog Metering
Circuit Breaker Two Pole
Battery isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford Pi044H
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop