

Model GK15S Type Heavy Duty Speed 1500 RPM Phase/Voltage 1, 240 Frequency 50 Hz Stdby Power 16.5kVA / 13.2 kVV Prime Output 15kVA / 12.0 kVV Fuel Capacity 100 Litres Length 1.93m Width 0.9m Height 1.3m Weight 770kg

Engine

Manufacturer Kubota Diesel
Engine Model D1703-BG
Type & Cylinder 4 Stroke – 3 L
Induction Naturally Aspirated
Fuel Consumption
3.8L @ 100%, 3.0L @ 75%, 2.1L @ 50% Load
Coolant Capacity 5.0 L
Governor Mechanical
Cubic Capacity 1.67 L
Oil Capacity 7.0 L

Outlets

Outlets Single Phase 3 x 15amp IP66 with RCB MCBO EBS PMG Option

Controls

Controller Remote Start with Analog Metering
Circuit Breaker Four Pole
Battery Isolator Fitted with canopy adjacent battery

Alternator

Alternator Brand / Model Stamford / Pi144E
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points Canopy Centre Lift, lockable doors with control panel viewing window Path Finish Heavy duty powder coat finish white canopy with a black base

Emergency Stop External Emergency Stop