



Genette

GK20S-1

Model GK20S
Type Heavy Duty
Speed 1500 RPM
Phase/Voltage 1, 240
Frequency 50 Hz

Stdby Power 22kVA / 17.6 kW
Prime Output 20kVA / 16 kW
Noise Level (dBA @ 7m) 57 dBA(A)
Fuel Capacity 100 Litres

Length 2.13m
Width 0.9m
Height 1.3m
Weight 870 kg

Engine

Manufacturer Kubota Diesel
Engine Model V2203-BG
Type & Cylinder 4 Stroke – 4 L
Induction Naturally Aspirated
Fuel Consumption
4.0L @ 100%, 3.2L @ 75%, 2.4L @ 50% Load
Coolant Capacity 8.2 L
Governor Mechanical
Cubic Capacity 3.9 L
Oil Capacity 9.7 L

Outlets

Outlets Single Phase
3 x 15amp IP66 with RCD MCBO
EBS PMG Option

Controls

Controller Remote Start with Analog Metering
Circuit Breaker Four Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford / Pi144H
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop Fitted