

Model GK20S Type Heavy Duty Speed 1500 RPM Phase/Voltage 3, 415 Frequency 50 Hz Stdby Power 22kVA / 17.6 kW Prime Output 20kVA / 16 kW Noise Level (dBA @7m) 57 dBA(A) Fuel Capacity 140 Litres Length 2.24m Width 1.02m Height 1.35m Weight 1021 kg

Engine

Manufacturer Kubota Diesel Engine Model V2203-BG Type & Cylinder 4 Stroke – 4 L Induction Naturally Aspirated Fuel Consumption 4.0L @ 100%, 3.2L @ 75%, 2.4L @ 50% Load Coolant Capacity 8.2 L Governor Mechanical Cubic Capacity 3.9 L Oil Capacity 9.7 L

Outlets

Outlets 3 Phase 1 x 32amp IP66 with CB Outlets Single Phase 3 x 15amp IP66 with RCD MCBO EBS PMG Option

Controls

Controller Remote Start with Analog Metering Circuit Breaker Four Pole Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford / Pi144H Type Brushless Harmonic Distortion Less than 5% Protection Class IP 23 Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points Canopy Centre Lift, lockable doors with control panel viewing window Path Finish Heavy duty powder coat finish white canopy with a black base Emergency Stop External Emergency Stop Fitted