

Model GK30S Type Heavy Duty Speed 1500 RPM Phase/Voltage 1, 240 Frequency 50 Hz Stdby Power kVA / kW 33kVA / 26kVV Prime Output kVA / kW 30 kVA / 24kVV Noise Level (dBA @7 m) 71dBA(A) Fuel Capacity 180 Litres Length 2.3m Width 1.15m Height 1.55m Weight 1276 kg

Engine

Manufacturer Kubota Diesel
Engine Model V3300-BG
Type & Cylinder 4 Stroke – 4 L
Induction Naturally Aspirated
Fuel Consumption
7.7L @ 100%, 5.9L @ 75%, 4.2L @ 50% Load
Coolant Capacity 8.2 L
Governor Mechanical
Cubic Capacity 3.9 L
Oil Capacity 13.2 L

Outlets

Outlets Single Phase 3 x Single phase Protection RCD/ELCB IP66 EBS PMG Option MX341 or MX321

Controls

Controller Remote Start with LCD Display Circuit Breaker Four Pole Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford UCi224D
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets
and skid tie down points
Canopy Centre Lift, lockable doors with control panel
viewing window
Path Finish Heavy duty powder coat finish white

canopy with a black base

Emergency Stop External Emergency Stop Fitted