



GKDWS200E



PORTABLE POWER



Relentless Power. Legendary Performance.



Technical

Model Type Speed Phase/Voltage Frequency Power kVA / kW Welder Duty Cycle 60% Strike Voltage Compressor Compressor Tank Size Battery Charger Engine	GKDWS200E Portable 3000 RPM 1/240 50 Hz 7.0kVA / 5.6kW 180 amp AC 75 V 196 LPM 2 Hp 25 litres 12 VDC 10 amp
Manufacturer Engine Model Starting Fuel Run Time Consumption Tank Capacity HP 3000 rpm max Cubic Capacity Oil Capacity Alternator	Kohler KD440 Electric start Diesel 5.3 hr 0.93 L/h @75% 5.0 L 10.9 442 Cm3 1.5 L
Alternator Brand Type Harmonic Distortion Protection Class Insulation Class Dimensions & Weight	Sincro Brushless Less than 5% IP 23 Class H
Length Width Height Weight Accessories	96 Cm 70 Cm 70 Cm 135 Kg
Width Height Weight Accessories Outlet Leads Options	96 Cm 70 Cm 70 Cm 135 Kg 10amp + 15amp switched with thermal overload 5m welding leads with hand piece & earth clamp
Width Height Weight Accessories Outlet Leads	96 Cm 70 Cm 70 Cm 135 Kg 10amp + 15amp switched with thermal overload

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.