



Genelite



PLGCM28S-1

Model PLGCM28S-1
Speed 1500 RPM
Phase/Voltage 1, 240
Frequency 50 Hz

Stdby Power 30kVA / 24 kW
Prime Output 28kVA / 22 kW
Noise Level @ 7m 72 dB(A)
Fuel Capacity 250 Litres

Length 2.460m
Width 1.01m
Height 1.695m
Weight 1448 kg

Engine

Manufacturer Cummins Diesel
Engine Model 4B3.9G1
Type & Cylinder 4 Stroke – 6 L
Induction Naturally Aspirated
Fuel Consumption
6.7L @ 100%, 5.2L @ 75%, 4.0L @ 50% Load
Coolant Capacity 8 L
Governor Mechanical
Cubic Capacity 3.9 L
Oil Capacity 11 L

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre lift, lockable doors with control panel viewing window
Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External

Controls

Controller DeepSea 7320 with LCD Metering
Circuit Breaker Single Pole
Battery Isolator Included
Battery Charger 24vDC 5amp

Alternator

Alternator Brand / Model Mecc Alte ECP32-3S4
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Options

Outlets Single Phase Options
PMG EBS option
Mine spec
Synchronising controls
Jacket water heater
Auto transfer switch options

CALL US
1300 305 912