

Distributed by:



HORVET 201D 3000 psi • 15 l/pm







Diesel Driven

Cold Water

Heavy Dut Usage

The Jetwave® Hornet™201D is a professional cold water diesel driven pressure washer that has stood the test of time. Australian engineered and assembled using only the best quality Italian and global components.



FIELDS OF APPLICATION

Cleaning Contractors
Boat Yards and Ports
Agricultural Equipment
Equipment Yards
Mining Industry



HERO INNOVATIONS



Optimise

6 x anti-vibration protection for quieter performance.



Durable

Foam filled 14" puncture proof tyres.

STANDOUT FEATURES



Professional Italian triplex Interpump delivers performance and longer life.



World class YANMAR® L100 diesel air-cooled engine.



Easy electric key start with maintenance free battery.



Dual M22 screw hose coupling system.



Oversized brass washable inlet water filter.



Pump rubber foot mounted.



Jetwave Safety System™ (JSS) thermal valve to prevent overheating in excessive bypass and over pressurisation.



Integrated accessory storage for hose, gun and lance.



Low speed professional pump for increased reliability and longer maintenance intervals.



Professional line accessories.



Quality pressure gauge.



Jetwave Group

72–74 Richmond Road
Keswick I Adelaide
South Australia I 5035 I AU

+61 8 8371 3599

sales@jetwave.com.au

jetwave.com.au

Robust - Welded hot dipped galvanised frame with convenient gun and lance holder.

Quality - Industry proven 'Italian' pump.



Power - YANMAR® L100 diesel air-cooled engine.

Portability -Heavy duty foam filled wheels.

			Idaili litted wileets.			
	Product Code	p/n	HP201-15D			
	TECHNICAL DATA					
l Iuty	Working Pressure	psi / bar	3000 / 200			
ance	Flow Rate	l/pm	15			
	Max Water Inlet Temp	°c / °f	60 / 140			
	INTENDED APPLICATION					
zzle	Usage Frequency	hours / type	4 - 8 daily / Constant			
steel with	Category of Dirt / Debris	type	Medium			
essure nplete	MOTOR FEATURES					
ned	Engine	type	YANMAR® L100 Diesel Engine			
	Power	hp	10			
n of	Fuel Supply	type	Diesel			
e wire	Fuel Capacity	litres	5.4			
se with ling.	Low Oil Shutdown	y / n	Υ			
	Starting System	type	Electric key start			
	HYDRAULIC FEATURES					
	Pump / Head / Pistons	type	Interpump Plunger Triplex / Brass / Ceramic			
WA160	Motor Pump Coupling	type	Gearbox Drive			
2001	Pump Speed	rpm	1450			
6105000	Unloader Valve	type	Independent (zero)			
1071	Safety Valve	y / n	Υ			
WA221	Orifice / Nozzle	size	045			
060CMPL	OTHER FEATURES					
OUOCMF L	Adjustable Pressure	y / n	Υ			
OCFSCP20	Hose Reel Provision	y / n	Υ			
	Frame Structure	type	Welded hot dipped galvanised 4 wheel roll			
OCFSCS22Z	Onboard Accessory Storage	y / n	Υ			

	Number per Pallet	type: pieces	AS: 2 / Euro: 1	
	WARRANTY(S)			
	Engine Warranty	years	2	2 100
	Limited Pump Warranty	years	2	2
	Limited Frame Warranty	years	5	5 100
	Limited Accessory Warranty	days	90	90 500

Y - Downstream low pressure adjustable

125 unit / 129 boxed

1110(L) x 700(W) x 860(H)

970(L) x 600(W) x 670(H)

y / n

kg

mm

mm

Detergent Injector

Approx Weight

Unit Dimensions

Boxed Dimensions

DIMENSIONS & WEIGHT

STANDARD EQUIPMENT



OPTIONAL ACCESSORIES

1. Complete Turbo Head with Lance	p/n	JWA160
2. Additional High Pressure Hose (per metre)	p/n	52001
3. High Pressure Swivel	p/n	26105000
4. 15m Extension Hose	p/n	41071
5. LS3-1 Foaming Lance with Tank	p/n	JWA221
6. High Pressure Hose Reel (cap 30m)	p/n	1060CMPL
7. Hammerhead™ Whirlaway 20" ABS	p/n	DCFSCP20
8. Hammerhead™ Whirlaway 22" Stainless Steel	p/n	DCFSCS22Z
9. Engine Hour Meter	p/n	ACD TACHO
10. Giraffe™ Telescopic Lance	p/n	DCLTG24A4
11. Sandblasting Kit	p/n	JWA164
12. Sludge Kit	p/n	80005
13. Drain Kit	p/n	ZDRAINKIT



The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement.

^{*}Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).