

Distributed by:



HIGH PRESSURE CLEANERS

HUSFLER[™]200 3000 psi • 11 l/pm







Frequent Usage

The Jetwave[®] Hustler[™] 200 is the perfect small cold water petrol powered by HONDA[™] pressure washer for cleaning yards and equipment. Australian engineered and assembled using only the best quality Italian and global components.



STANDOUT FEATURES



Professional Italian triplex Interpump delivers performance and longer life.



Easy start HONDA™ GX200 Industrial Series OHV



Dual M22 screw hose coupling system.



0-30° variable spray patterns hi-lo (soap) nozzle.



Brass washable inlet water filter.

Jetwave Safety System™ (JSS) thermal valve to prevent overheating in excessive bypass and over pressurisation.



Professional line accessories.

FIELDS OF APPLICATION

Cleaning Contractors Agricultural Equipment Car and Equipment Yards Concrete and Landscaping Motorcross Bike Wash-down Household and Path Cleaning





Engine.



STANDARD EQUIPMENT



Hose - 10m of 3/8" wire braided hose with quick coupling.

OPTIONAL ACCESSORIES

1. Complete Turbo Head with Lance	p/n	JWA158
2. Additional High Pressure Hose (per metre)	p/n	52001
3. High Pressure Swivel	p/n	26105000
4. 15m Extension Hose	p/n	41071
5. LS3-1 Foaming Lance with Tank	p/n	JWA221
6. High Pressure Hose Reel (cap 30m or 60m)	p/n	1060CMPL 1065CMPL
7. Engine Hour Meter	p/n	19598
8. Giraffe™ Telescopic Lance	p/n	DCLTG24A4
9. Sandblasting Kit	p/n	JWA029
10. Sludge Kit	p/n	80005
11. Drain Kit	p/n	ZDRAINKIT



The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement. Robust - Welded hot dipped galvanised frame.

Quality - Industry proven 'Italian' pump.



Ergonomics - 4 wheel trolley frame designed for durability.

Power - HONDA™ GX200 engine.

Portability - Heavy duty double bearing pneumatic wheels.

Product Code	p/n	HP200-11P		
TECHNICAL DATA	TECHNICAL DATA			
Working Pressure	psi / bar	3000 / 200		
Flow Rate	l/pm	11		
Max Water Inlet Temp	°c / °f	60 / 140		
Class	grade	A (AS/NZS 4233.1:2013)		
INTENDED APPLICATION				
Usage Frequency	hours / type	2 daily / Intermittent		
Category of Dirt / Debris	type	Light		
MOTOR FEATURES				
Engine	type	HONDA™ GX200 (4 stroke, air cooled)		
Power	hp / cc	6.5 / 200		
Fuel Supply	type	Unleaded		
Fuel Capacity	litres	3.1		
Low Oil Shutdown	y / n	Y		
Starting System	type	Recoil / Pull		
HYDRAULIC FEATURES				
Pump / Head / Pistons	type	Interpump Plunger Triplex / Cast (nickel plated) / Ceramic		
Motor Pump Coupling	type	Direct Drive		
Pump Speed	rpm	3400		
Unloader Valve	type	Integral		
Safety Valve	y / n	Y		
Orifice / Nozzle	size	035		
OTHER FEATURES				
Electric / Key Start Available	y /n	N		
Adjustable Pressure	y / n	Y		
Hose Reel Provision	y / n	Υ		
Frame Structure	type	Welded hot dipped galvanised 4 wheel roll		
Onboard Accessory Storage	y / n	Y		
Detergent Injector	y / n	Y - Downstream low pressure adjustable		
DIMENSIONS & WEIGHT				
Approx Weight	kg	42 unit / 46 boxed		
Unit Dimensions	mm	700(L) x 600(W) x 920(H)		
Boxed Dimensions	mm	640(L) x 600(W) x 580(H)		
Number per Pallet	type: pieces	AS: 4 or 8 / Euro: 2 or 4		
WARRANTY(S)				
Engine Warranty	years	4 CYEAR		
Limited Pump Warranty	years	2		
Limited Frame Warranty	years	5		
Limited Accessory Warranty	days	90		
*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).				