

Distributed by:

Brick Cleaning

Run-about Jobs

Concrete and Trade
Council Applications
Agricultural Equipment

FIELDS OF APPLICATION



3LACCGC 3300 psi • 9.1 l/pm







Petrol Driven

Cold Water

Occasior Usage

The Jetwave® Black™ GC is the perfect, premium residential, small cold water petrol powered by HONDA™ pressure washer for cleaning yards and equipment. Engineered and assembled in the USA.



STANDOUT FEATURES



OEM[™] sealed axial pump delivers performance and longer life.



World class HONDA™ GC190 Series OHV Engine.



Dual M22 screw hose coupling system.



Water inlet filter.



Brass pump head with ceramic coated pistons.



Jetwave Safety System™ (JSS) thermal valve to prevent overheating in excessive bypass.



Ergonomic spray gun for comfort and control.



0°, 15, 25, 40 and soap snap-on brass nozzles.



Jetwave Group

72–74 Richmond Road
Keswick I Adelaide
South Australia I 5035 I AU

+61 8 8371 3599

sales@jetwave.com.au

jetwave.com.au

STANDARD EQUIPMENT



Spray Gun -Heavy duty back part lance with side grip.






Hose - 8m of 3/8" steel braided hose with quick coupling.

OPTIONAL ACCESSORIES

1. Complete Turbo Head with Snap Tail	p/n	Included
2. 15m Extension Hose + M22 Joiner	p/n	40290C
3. LS3-1 Foaming Lance with Tank	p/n	JWA221
4. 15" Whirlaway (Steel)	p/n	71008237



Ergonomics - 2 wheel trolley frame designed for durability.

Power - HONDA™ 190cc OHV engine.

Portability - Heavy duty double bearing pneumatic wheels.

Product Code	p/n	CW3300-9.1P	
TECHNICAL DATA			
Working Pressure	psi / bar	3300 / 230	
Flow Rate	l/pm	9.1	
Max Water Inlet Temp	°c / °f	60 / 140	
Class	grade	Α	
INTENDED APPLICATION			
Usage Frequency	hours / type	1-2 daily / Intermittent	
Category of Dirt / Debris	type	Light	
MOTOR FEATURES			
Engine	type	HONDA™ GC190 (4 stroke, air cooled)	
Power	hp / cc	6 / 190	
Fuel Supply	type	Unleaded	
Fuel Capacity	litres	2	
Low Oil Shutdown	y / n	N	
Starting System	type	Recoil / Pull	
HYDRAULIC FEATURES			
Pump / Head / Pistons	type	Axial (OEM) / Brass / Ceramic Coated	
Motor Pump Coupling	type	Direct Drive	
Pump Speed	rpm	3400	
Unloader Valve	type	Integral	
Powerboost	y / n	Υ	
Orifice / Nozzle	size	03	
OTHER FEATURES			
Adjustable Pressure	y / n	N	
Hose Reel Provision	y / n	N	
Frame Structure	type	Heavy duty steel 2-wheel trolley	
Onboard Accessory Storage	y / n	Υ	
Detergent Injector	y / n	Y - Downstream low pressure	
DIMENSIONS & WEIGHT			
Approx Weight	kg	36 unit / 40 boxed	
Unit Dimensions	mm	800(L) x 520(W) x 580(H)	
Boxed Dimensions	mm	540(L) x 650(W) x 600(H)	
Number per Pallet	type: pieces	AS: 4 / 8 or 12 / Euro: 2 or 4	
WARRANTY(S)			
Motor Warranty	year	1 Engine KARCANY	
Warranty	year	1 TYPE	
		<u>₩</u>	



The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement.