## **Semi-Industrial Models** Silent 122 & K1152TST





## Theres nothing small about the Power Packs!

High quality, high performance units designed for use in light to medium industrial usage. Operates up to 1885psi (3700epsi) with a water flow of 10 litres per minute. Ideal for house painters, farmers and vehicle cleaning.

## **FAQ**

Why is the K1152TST a small power pack? This unit comes standard with a built in hose reel and a Dirtkiller. Boosting the effective working pressure to 3,200psi, it can handle any medium sized job!

What is the advantage of a steel braided hose? Lasts longer than fabric braid - non kinking.



Integrated trolley takes steps and rough ground in its



drum with foldable crank and 15 m steel braided highpressure hose



5m power cord with cable reel





Dirtkiller lance with stainless steel pipe, Vario-Jet lance with stainless steel pipe and fully adjustable spray jet angle from pencil to wide fan as well as high and low pressure



Silent 122 Quiet, slow running 1400rpm

Technical Data	Silent 122	1152TST	
Order no. with Dirtkiller	KM412211	KM412181	
Operating pressure, continuously adjustable	30-120 bar 435-1740psi	30-130 bar 435-1885psi	
Max. admissible overpressure	135 bar	150 bar	
Water output	7 l/min. (600 l/h)	10 l/min. (600 l/h)	
Inlet water temperature	max. 60 °C	max. 60 °C	
Nozzle size, Dirtkiller	028	042	
Nozzle size, vario jet nozzle	028	042	
Motor speed	1,400rpm	2,800rpm	
Connected load	240V, 7.5A, 50Hz	230V, 12A, 50Hz	
Power intake	1.6 kW	2.8 kW	
Power output	1.0 kW	2.0 kW	
Weight	26 kg	31.5 kg	
Dimensions (L x W x H) in mm	300 x 330 x 800	360 x 365 x 870	

O Colour coding indicating nozzle size

Features and Equipment	<b>S122</b>	1152
Easy-start - NEW!		•
Total-Stop system	0	•
Low pressure detergent	0	•
Hose drum with HP hose, 15 m NW 6	0	•
Steel braided high- pressure hose, <b>10 m</b> NW 6	•	0
Trigger gun with safety catch 'M2000'	•	•
Dirtkiller lance with stainless steel pipe	•	•
Vario jet lance with stainless steel pipe	•	•
Water intake filter	0	0

Standard Equipment
Option