

# **Cold Water High Pressure Cleaners**

Industrial Quadro - Single Phase



Technical Data	WS599TS
Part Number	WS599TS
Operating pressure, continuously adjustable	30 - 150 bar, 435-2175 psi
Max. admissible overpressure	165 bar, 2392psi
Water output	10 L/min.
Inlet water temperature	max. 60 °C
Suction height	2.5m
Nozzle size, Dirtkiller	035
Nozzle size, flat jet nozzle	20035
Motor speed	1400 rpm
Connected load	230 V, 12.0 A, 50 Hz
Power intake	3.3 kW
Power output	2.4 kW
Weight	55 kg
Dimensions (L x W x H) in mm	680 x 440 x 520 mm

Features and Equipment	WS599TS
Total-Stop system	•
Safety cut-out	•
High pressure detergent	•
Sted Braided high pressure hose 10m	•
Trigger gun with safety catch 'Starlet'	•
Dirtkiller lance with stainless steel pipe	0
Flat jet lance with stainless steel pipe	•
Water intake filter	0

Standard Equipment O Option

Efficient and powerful single phase cleaner. Latest technology and high pressure detergent system gives 30% more cleaning power than competitors' models - up to 3050 EPSI cleaning power with 'Dirt Killer' turbo nozzle included!

- Adjustable pressure control
- Graphite packed seals for dry-run safety
- Brass pump head and ceramic coated pump pistons
- 1400rpm for a lifetime of reliability
- Single phase 15amp

### **Optional Accessories**

### **Underbody Lance**

800mm Extension (#41075)



#### **Dirt Killer Nozzle & Lances**

800mm Extension (#41075)



## **Pipe Cleaning Hose w/Nozzle**

15m - (#41058) 20m - (#410582) 30m - (#410584)

# **Rotary Washbrush**

M22, ST30 Nipple (#410501)



#### **Wire Braided High Pressure Hose**

