



OzPOWER

POWER EQUIPMENT



OZPower+ 30S

Model OZGPC28S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz
Power Factor .8

Stdby Power 30kVA / 24kW
Prime Output 28kVA / 22kW
Noise Level (dBA @ 7 m) 67dB(A)
Fuel Run Time 24 Hours

Length 2.45 m
Width 1.08 m
Height 1.865 m
Weight 1350 kg

Engine

Manufacturer Cummins Diesel
Engine Model 4B3.9G1
Type & Cylinder – 4 Stroke - 4 L
Induction Naturally Aspirated
Fuel Consumption 6.7 L @ 100%
5.2 L @ 75%, 4.0 L @ 50% Load
Coolant Capacity 8 L
Governor Electronic
Cubic Capacity 3.9 L
Oil Capacity 11 L
Warranty World Wide as per 3381307 Publication

Alternator

Alternator Brand / Model OEM AVR Controlled
Type Brushless
Harmonic Distortion Less than 3%
Protection Class IP 23
Insulation Class Class H

Controls

Controller SmartGen 6120 with LCD Display
Circuit Breaker 3 Pole
Battery Isolator Fitted with canopy adjacent battery

Canopy

Skid Base fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Paint Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop Fitted

Options

Outlets 1 x 32 AMP 3 Phase / 2 x 15 AMP Single Phase Weatherproof IP66