

The "TRASHMATE" Series are rugged lightweight dirty water transfer pumps, ideal for construction and civil engineering applications. These pumps are complete with quick action release front casings for 100% accessability to clear blockages, silicon carbide seals and high chrome impellers along with spheroidal graphite iron castings. The high-quality HONDA engine ensures a long operational life span and Koshin's guaranted specifications give peace of mind performance.


ADVANTAGES

- · Rugged and lightweight.
- · Hose fittings and strainer.
- Genuine HONDA engine.
- · Japanese quality.
- Roll cage for ease of handling & transport.

APPLICATIONS

- · Water transfer
- Site pumping
- Irrigation
- **Sprinklers**
- Agriculture
- Mine site de-watering







PERFORMANCE TABLE

PUMP					ENGINE					
MODEL	MAX. FLOW	MAX. HEAD	MAX. SUCTION LIFT	SUCTION / DISCHARGE CONNECTION	TYPE	MODEL	RATED OUTPUT	FUEL TANK CAPACITY	CONT. RUN TIME	STARTER METHOD
KTH-50X	700 L/min	30m	8m	2" BSP (50mm)	4 Stroke	Honda - GX160	2.9kW / 3600rpm	3.1L	2.2hrs	Recoil
KTH-80X	1340 L/min	27m	8m	3" BSP (80mm)	4 Stroke	Honda - GX240	4.6kW / 3600rpm	5.3L	2.5hrs	Recoil
KTH-100X	1600 L/min	25m	8m	4" BSP (100mm)	4 Stroke	Honda - GX340	5.8kW / 3600rpm	6.1L	2.0hrs	Recoil